

CAT-RAP™

CATALYTIC CONVERTER SECURITY

Parts List

- A. Stainless Steel Security Plates with
 - a. Eleven (11) pre-installed hex head screws
 - b. Four (4) torx security screws
 - c. Four (4) slotted set-screws
- B. Two (2) 17.5 foot lengths of Stainless-Steel Cable
- C. Stainless Steel Cover
- D. Security Torx Bit


Recommended Tools

- Safety Glasses
- Work Gloves
- Impact Drill or Wrench with 7/16" socket
- Flat Head Screwdriver



The CAT-RAP™'s unique design allows it to accommodate a wide variety of vehicle types and Catalytic Converter (CAT) positions (*i.e., vertical vs. horizontal*). There are many ways to install your CAT-RAP. The intent of this theft deterrent is to confuse, frustrate and create enough time or hassle that a thief will ultimately look for an easier target. The more wraps made around the CAT, exhaust pipe and vehicle frame, the more secure your CAT will be.

Figure 1



WARNING #1: Due to extreme temperatures, do not attempt installation or modification of the CAT-RAP within five (5) hours of vehicle operation.

Note: Start in the middle and wrap outward. A minimum of 3 to 4 wraps is recommended around the center and each end of the exhaust pipe.

PATENT PENDING



CABLE WRAPPING STRATEGY: The CAT-RAP's security plate system is designed to be universal and adapt to most vehicles with easily accessible catalytic converters. The CAT-RAP allows for up to 20 individual security loops as the cable can be inserted through each plate channel up to two times. As the cable passes through the plates, it creates secure, individual loops around the CAT and vehicle frame. Once tightened, if one loop is tampered with, the remaining loops will not be affected.

The best strategy is to utilize a sequence of tight wraps combined with looser wraps. The looser the cable, the harder to cut. However, be sure to adhere to the WARNING (#2) message below. It is recommended to start with 3-4 tight wraps first in the middle of the CAT and working your way to one side. Then use the remaining cable to create a series of looser wraps that surround the CAT and secure to the vehicle frame.

WARNING #2: All vehicles have unique undercarriage configurations. Make sure CAT-RAP and/or Cable is NOT touching, pinching, or compromising any electrical wires, brake lines, heat shields and/or critical drive train components. Also be sure the CAT-RAP or any cable is not hanging lower than any other part of the vehicle undercarriage before final tightening of the security plates.

INSTALLATION:

To ensure maximum security, it is recommended to have 3-to-4 wraps "tightly" around the middle of the CAT first to hold the device firmly in place during installation. This will also help eliminate any potential for vibration and/or road noise.

1. Read WARNING (#1) to ensure the vehicle is install ready. Then position Security Plates (*Part A*) under the Catalytic Converter (CAT) with the screw heads facing away from the CAT (*i.e. make sure they are accessible to tighten after routing the cable*).
2. While holding the security plates against the CAT, insert "un-ferruled" end of **CABLE ONE** (*Part B*) through the center channel (*see Figure 1*) of the security plates. Pull all the way through until the cable stops against the "ferruled" end.
3. Wrap the "un-ferruled" end tightly around the CAT and route through an adjacent channel in the security plates. Continue wrapping from the center working your way to one end of the CAT. (*Refer to Figure 1*)
4. Once you reach one end of the CAT, make a series of 2-to-4 tight wraps around the exhaust pipe where it is connected to the CAT. Then wrap the remaining cable a little looser (*allowing it to flex 1-2 inches each way*) alternating between the CAT and vehicle frame. Continue wrapping the cable around the CAT/Vehicle Frame (*Refer to Figure 1*) until there is only 2-to-3 inches of cable remaining after final insertion into the security plates.
5. **CABLE TWO:** Repeats steps 1-4 with the second cable but this time wrapping in the opposite direction. Just as before, start in the middle. **Please note: some vehicles may only require one length of cable to complete the install.**
6. Once the wrapping is complete, verify that you have at least 3-4 wraps total around the CAT; 3-4 wraps tightly around each side of the exhaust pipe where it connects to the CAT and 3-4 loose wraps around the frame. Be sure to adhere to the WARNING (#2) above before moving to step 7.
7. Tighten security plates with impact drill or wrench using a 7/16" hex socket.
8. Attach/align cover plate (*Part C*) over the four (4) slotted set-screws. Using a flat head screwdriver, remove the slotted set-screws one-at-a-time (*to maintain alignment*) and replace with the four (4) torx security screws using the provided bit (*See Figure 2*).

The CAT-RAP™ is covered by a one (1) year warranty. Warranty does not extend to the cost of a replacement converter.

Figure 2 - Completed Install



**FOR ADDITIONAL ASSISTANCE, CHECK
OUT OUR INSTALLATION VIDEOS ON
WWW.FREIGHTDEFENSE.COM**



FREIGHT DEFENSE
SECURITY FOR THE LONG HAUL

PATENT PENDING



LIMITED WARRANTY TERMS & CONDITIONS

FREIGHT DEFENSE

Toll Free: (855) 935-9999 • 1271 Contract Drive • Green Bay, WI 54304 • customerservice@freightdefense.com

INSTALLATION

Freight Defense, LLC is not responsible for installing their represented products or for the harm suffered by any person as a result installing it.

WARRANTIES

a) Customer acknowledges that it is unreasonable to believe that any device whatever will prevent a theft in the case of every attempt and that the most that can be expected from a so-called anti-theft or security device is that it will deter many thieves.

b. FREIGHT DEFENSE, LLC MAKES, AND CUSTOMER RECEIVES, NO WARRANTY, EXPRESSED OR IMPLIED, EXCEPT THE WARRANTIES OF TITLE TO THE FREIGHT DEFENSE PRODUCT AND THEIR MERCHANTABILITY, PARTICULARLY NO WARRANTY OF FITNESS FOR A PARTICULAR USE OR PURPOSE OR AGAINST INFRINGEMENT.

c. As Customer's only remedy, Freight Defense, LLC will repair or replace, at its option and without charge, a Freight Defense product that is defective in material or workmanship when received by Customer and is returned to Freight Defense, LLC, FOB Freight Defense's offices, within one (1) year after date of purchase by the Customer. Freight Defense, LLC will ship all replacement, or repaired, products to Customer, FOB Freight Defense's shipping point.

d. Freight Defense will honor a 30 day return policy from date of purchase (proof of purchase required). Please note, all returns will be subject to a 25% restocking fee and product must be in good working order and free from defects. Freight/shipping charges are not included in the return policy. Customer is responsible for all freight/shipping charges with respect to product returns. In order to make a warranty claim, please contact Customer Service to receive a Return Merchandise Authorization (RMA) Number.

e. Factory support is only available for Freight Defense products purchased as new through an Authorized Freight Defense dealer. Please Note: Freight Defense products purchased on auction sites such as Ebay and Craigslist, to name a few, will not be covered under factory warranty under any circumstance. Freight Defense, LLC is unable to verify whether products sold through Auction Sites are new, used, or refurbished, and as such, Freight Defense, LLC is unable to warranty such purchases. Freight Defense, LLC advises using extreme caution when buying through auction sites as you'll be doing so at your own risk.

NO LIABILITY

Freight Defense, LLC is not liable for any loss or damage claimed by Customer or any third person to have been suffered or incurred as a result or, or related to, the products purchased under this Agreement, regardless of the circumstances or form of action, except any bodily injury or death for which Freight Defense, LLC is liable under productsliability law. Without limiting the generality of the foregoing, in no event will Freight Defense, LLC be liable to Customer for any indirect, special, or consequential damages, regardless of the circumstances or the cause of action, particularly not for the value of a vehicle, or any other money damages in the event that a theft occurs either notwithstanding the use of a Freight Defense product or when it has been returned for repair or replacement.

END OF TERMS AND CONDITIONS



FREIGHT DEFENSE LIMITED WARRANTY FORM

Please complete and mail or email (customerservice@freightdefense.com) this form to record your warranty with the manufacturer.

NAME _____

ADDRESS _____ CITY _____ STATE _____ ZIP _____

TELEPHONE _____ EMAIL _____

FREIGHT DEFENSE PART NUMBER _____ VEHICLE MAKE _____ MODEL _____ YEAR _____

COMMENTS / NEW PRODUCT IDEAS / ETC: _____

Please mail completed warranty form (above) in self addressed envelope to:
Freight Defense LLC • 1271 Contract Drive • Green Bay, WI 54304

Alternatively, you may email the information above to customerservice@freightdefense.com. Please type "Warranty Form" in the email subject line.

PATENT PENDING